

## Aztec® StrongBack Slab / Beam Bolster™ - PSBB



### APPLICATION:

Elevated Slab, Tilt-Wall, Precast, Post-Tension, Parking Garage Decks, Side-Form Spacer

### COVER HEIGHT:

From 3/4" to 3" (1/4" Increments)

### FEATURES:

- High load strength and impact resistant
- Qualifies for use as a Beam Bolster with 2-1/2" leg spacing
- Can be used individually or locked together to create any length
- Manufactured in 30" lengths in standard boxes
- Special packaging available in 5' or 10' sections, bundled and palletized

PRODUCT CODE	COVER	FT./BOX	QTY/BOX	WT.LBS. PER BOX
123570	3/4"	250	100	25
123571	1"	225	90	25
123572	1-1/4"	225	90	26
123573	1-1/2"	200	80	23
123574	1-3/4"	150	60	21
123575	2"	150	60	22
123576	2-1/4"	125	50	20
123577	2-1/2"	100	40	17
123578	2-3/4"	100	40	18
123579	3"	100	40	19



Meets all requirements to qualify as a CRSI Class 1 Bar Support.

## Aztec® StrongBack SBU™ Slab Bolster Upper - PSBU



### APPLICATION:

Supports top layer in Double Mat application, Rebar or Wire Mesh, Slabs, Heavy Duty On-Grade, Corrugated Decking, Side-Form Spacer-below-grade applications only, Precast

### COVER HEIGHT:

From 1" to 5" (1/4" increments)

### FEATURES:

- Designed for use with Epoxy-Coated/FRP/ Stainless Steel/Galvanized rebar
- For use in corrosive environments
- Spans corrugations in elevated deck applications
- Suitable for use on Vapor Barriers or Insulating Foam
- No overlap required
- Manufactured in 30" lengths in standard boxes
- Special packaging available in 5' or 10' sections, bundled and palletized
- Strong as metal SBU

PRODUCT CODE	COVER	FT./ BOX	QTY/BOX	WT. LBS. PER BOX
220165	1"	100	40	40
220335	1-1/4"	100	40	40
220166	1-1/2"	75	30	30
220312	1-3/4"	75	30	30
220167	2"	75	30	30
220313	2-1/4"	75	30	30
220297	2-1/2"	50	20	20
220314	2-3/4"	50	20	20
220296	3"	50	20	20
220315	3-1/4"	50	20	20
220384	3-1/2"	50	20	20
220461	3-3/4"	50	20	20
220382	4"	50	20	20
220462	4-1/4"	38	20	20
220385	4-1/2"	38	20	20
220463	4-3/4"	38	20	20
220386	5"	38	20	20



Meets all requirements to qualify as a CRSI Class 1 Bar Support.

## Aztec® E-Z Lok Slab Bolster™ - PSB



### PATENTED

### APPLICATION:

Precast

(For Slabs, Side-Form Spacers, Tilt-Wall and D.O.T. applications, refer to STRONG-BACK BOLSTER™)

### COVER HEIGHT:

From 3/4" to 3"

### FEATURES:

- Manufactured in 32" lengths in standard boxes
- Can be used individually or snapped together to create any length
- Capable of bending to 180 degrees
- Simple to install, non-corrosive and lightweight

PRODUCT CODE	COVER	FT./BOX	QTY/BOX	WT. LBS. PER BOX
78016	3/4"	325	122	33
78026	1"	275	103	27
78036	1-1/4"	250	94	30
78046	1-1/2"	200	75	25
78056	1-3/4"	200	75	23
78066	2"	150	56	22
78076	2-1/4"	150	56	24
78086	2-1/2"	125	47	23
78091	2-3/4"	125	47	24
78096	3"	125	47	25



Meets all requirements to qualify as a CRSI Class 1 Bar Support.